

2026, Jericho Design Group, LLC. These drawings are protected by the copyright laws of the United States. These drawings or any part thereof may not be used for any purpose or reproduced in any form or by any means without the written consent of Doug Shaw.

INTERIOR DOOR SCHEDULE																		
NO.	ELEVATION	DOOR					FRAME			DETAILS			FIRE RATING	HARDWARE SET	NOTES			
		SINGLE / PAIR	WIDTH	HEIGHT	THICK.	MATL.	FINISH	ELEVATION	MATL.	FINISH	HEAD	JAMB				SILL		
LEVEL 1																		
101	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		5			
102	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		12			
103	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		11			
104	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		10			
105	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		11			
106	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		10			
107	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		12			
109	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		10			
110	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		10			
111	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		10			
112	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		14			
113	FG	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	2	HM	PTD	H4/A-7.51	J5/A-7.51	--	1	13			
114	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		12			
116	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		13			
117	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		13			
118	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		13			
119	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		13			
120	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		9			
121	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		13			
122	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		13			
123	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		13			
124	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		11			
125	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		11			
126	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		12			
127	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		12			
128A	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		12			
128B	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		12			
129	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	2	HM	PTD	--	--	--		8			
131	F2	PAIR	6'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		6			
132A	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	2	HM	PTD	--	--	--		7			
132B	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		5			
134	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	2	HM	PTD	--	--	--		16			
138	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		10			
139	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		10			
224A	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		15			
224B	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		15			
302	G	SINGLE	3'-0"	6'-0"		ALUM	PF	--	ALUM	PF	--	--	--		18	CHAIN LINK FENCE		
303	G	SINGLE	3'-0"	6'-0"		ALUM	PF	--	ALUM	PF	--	--	--		18	CHAIN LINK FENCE		
LEVEL 2																		
201	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		5			
202	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		10			
203	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		12			
204	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		10			
206	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		5			
207	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		11			
208	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		11			
209	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		11			
210	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		11			
211	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		11			
212	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		11			
214	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		15			
215	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		12			
216	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		14			
218	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		12			
219	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		10			
220	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		13			
221	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		13			
222	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	1	HM	PTD	--	--	--		10			

EXTERIOR DOOR SCHEDULE																	
	DOOR						FRAME			DETAILS			FIRE RATING	HARDWARE SET	NOTES		
NO.	ELEVATION	SINGLE / PAIR	WIDTH	HEIGHT	THICK.	MATL.	FINISH	ELEVATION	MATL.	FINISH	HEAD	JAMB				SILL	
LEVEL 1																	
S100	FG	SINGLE	3'-0"	7'-0"	0'-1 3/4"	ALUM	PF	F2	ALUM	PF	--	--	--	3	- HINGES, FULL MORTISE, HVY WT - RIM EXIT DEVICE, PASSAGE - SURFACE CLOSER - KICK PLATE - DOOR STOP - GASKETING - SWEEP - THRESHOLD		
S101	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	2	HM	PTD	--	--	--	4			
S102	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	2	HM	PTD	--	--	--	2			
S103	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	2	HM	PTD	--	--	--	2			
S105	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	2	HM	PTD	--	--	--	2			
S106	OHD	PAIR	14'-0"	14'-0"	0'-2"	ALUM	PF	--	STL	PF	--	--	--	17			
S107	OHD	PAIR	14'-0"	14'-0"	0'-2"	ALUM	PF	--	STL	PF	--	--	--	17			
S108	OHD	PAIR	14'-0"	14'-0"	0'-2"	ALUM	PF	--	STL	PF	--	--	--	17			
S109	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	2	HM	PTD	--	--	--	4			
S110	OHD	PAIR	14'-0"	14'-0"	0'-2"	ALUM	PF	--	STL	PF	--	--	--	17			
S111	OHD	PAIR	14'-0"	14'-0"	0'-2"	ALUM	PF	--	STL	PF	--	--	--	17			
S112	OHD	PAIR	14'-0"	14'-0"	0'-2"	ALUM	PF	--	STL	PF	--	--	--	17			
S113	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	2	HM	PTD	--	--	--	4			
S301	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	2	HM	PTD	--	--	--	4			
S302	OHD2	PAIR	12'-0"	12'-0"	0'-2"	ALUM	PF	3	STL	PF	--	--	--	17			
S303	OHD2	PAIR	12'-0"	12'-0"	0'-2"	ALUM	PF	3	STL	PF	--	--	--	17			
S304	F	SINGLE	3'-0"	7'-0"	0'-1 3/4"	HM	PTD	2	HM	PTD	--	--	--	4			
LEVEL 2																	
S200	FG3	PAIR	6'-0"	7'-0"	0'-1 3/4"	ALUM	GL	--	ALUM	ANODZ	--	--	--	1		- HINGES, FULL MORTISE, HVY WT - RIM EXIT DEVICE, PASSAGE - SURFACE CLOSER - KICK PLATE - DOOR STOP - GASKETING - SWEEP - THRESHOLD	
S201	FG	SINGLE	3'-1"	6'-11"	0'-1 3/4"	ALUM	PF	F2	ALUM	PF	--	--	--	3			
S202	FG	SINGLE	3'-0"	6'-11"	0'-1 3/4"	ALUM	PF	F2	ALUM	PF	--	--	--	2			
S204	FG	SINGLE	3'-1"	7'-0"	0'-1 3/4"	ALUM	PF	F2	ALUM	PF	--	--	--	2			

GENERAL NOTES	ABBREVIATIONS LEGEND
* REFER TO GENERAL SHEET ADA REGULATORY DIAGRAMS FOR MORE INFORMATION 1. SEE GENERAL SPECIFICATIONS FOR DOOR AND FRAME FINISHES. 2. ALL DOOR HARDWARE SHALL BE HANDICAP ACCESSIBLE, COMPLYING WITH 2010 ADA STANDARDS FOR ACCESSIBLE DESIGN. 3. WHERE DISCREPANCIES OCCUR BETWEEN THE DOOR SCHEDULE NOTES AND HARDWARE SPECIFICATIONS, NOTIFY THE ARCHITECT OF DISCREPANCIES TO RECEIVE DIRECTION ON HOW TO PROCEED. 4. THE MAGNETIC LOCK INTO FIRE ALARM. 5. REFER TO THE PARTITION TYPE OR APPLICABLE WALL SECTION AND THEN TO TYPICAL DOOR DETAILS FOR APPROPRIATE DETAIL. 6. ALL EXTERIOR HOLLOW METAL DOORS TO BE INSULATED AND GALVANIZED. 7. ALL EXTERIOR DOORS TO BE WEATHER STRIPPED AND HAVE CLOSERS. 8. ALL FIRE RATED DOORS TO HAVE CLOSERS. 9. PROVIDE METAL TRANSITION STRIPS AT THE FOLLOWING FLOORING TRANSITIONS: WOOD/PORCELAIN, WOOD/CARPET, CARPET/PORCELAIN. 10. EACH EXTERIOR WINDOW AND DOOR SHALL BE LABELED BY THE MANUFACTURER TO CERTIFY COMPLIANCE WITH THE REQUIREMENTS OF THE NATIONAL FENESTRATION RATING COUNCIL PER NFRC 100-97 FOR FIELD VERIFICATION BY THE INSPECTOR. 11. THERMAL TRANSMITTANCE REQUIREMENTS: EACH EXTERIOR DOOR SHALL HAVE A MAXIMUM U-FACTOR OF 0.50. EACH EXTERIOR WINDOW SHALL HAVE A MAXIMUM U-FACTOR OF 0.35 AND MAX. SOLAR HEAT GAIN COEFFICIENT OF 0.25. 12. PROVIDE SEALANT JOINT ON ALL SIDES OF WINDOWS, BETWEEN WINDOW SYSTEM & DISSIMILAR MATERIALS, MIN. SIZE OF SEALANT JOINTS TO BE 1/2" OR PER WINDOW MANUFACTURERS STANDARDS, WHICHEVER IS GREATER. 13. FASTEN ALL METAL THRESHOLDS AND METAL EDGE STRIPS WITH 2" LONG STAINLESS STEEL SCREWS. SET EXTERIOR THRESHOLDS IN FULL BED OF MASTIC. 14. FOR INTERIOR TRANSITION AT DOOR SILL CONDITIONS, SEE INTERIOR DWGS. 15. SEE SPECIFICATIONS FOR ADDITIONAL HARDWARE INFORMATION.	DOOR MATERIAL TYPE ALUM - ALUMINUM HM - HOLLOW METAL PLAM - PLASTIC LAM CLAD SCWD - SOLID CORE WOOD GL - GLASS/GLAZING FINISH TYPE STD - STAIN PTD - PAINT PF - PREFINISHED/MANUFACTURE ANODZ - CLEAR ANODIZED FRAME MATERIAL TYPE ALUM - ALUMINUM HM - HOLLOW METAL STL - STEEL WD - WOOD GLAZING NOTES 1. ALL FRAMES IN EXTERIOR WALL CONDITIONS SHALL RECEIVE 1" INSULATING CLEAR (LOW E) GLASS UNITS. 2. ALL GLASS UNITS LOCATED WITHIN 24" OF DOOR(S) AND/OR WHERE BOTTOM EDGE IS LESS THAN 18" ABOVE THE FINISH FLOOR SHALL RECEIVE TEMPERED GLASS. G-2 TEMPERED GLASS UNITS IG-1 LOW E INSULATING GLASS IG-2 LOW E INSULATING TEMPERED GLASS P-1 POLYCARBONATE

DOOR HARDWARE SCHEDULE - SEE SPECIFICATIONS FOR DETAIL

SET 1 - EXTERIOR - ALUM - PAIR

LOBBY

- CONT. HINGES
- MANUAL FLUSH BOLT
- DUST PROOF STRIKE
- MORTISE DEADLOCK
- CYLINDER/CORE
- SURFACE CLOSER
- KICK PLATE
- THUMB TURN CYLINDER
- DOOR PULL
- EXIT PUSH BAR
- RAIN GUARD
- SWEEP
- WIRE HARNESS
- ADA POST W/ DOOR SWITCH
- DOOR POSITION SWITCH
- PIN PAD
- POWER SUPPLY

Notes:

- Balance of hardware: Threshold, door sweeps, perimeter and meeting stile gasket furnished by the aluminum storefront door and frame manufacturer.
- Coordinate all hardware with the aluminum storefront door/frame manufacturer/supplier.
- Provide necessary collars/rings, cams and tailpieces/spindles for all cylinders.
- Provide blocking/spacer rings in thickness as required to fill gap, if any, between cylinder head and face of door.
- Provide necessary drop plates and fillers for proper installation of door closers.
- Verify finish of hardware.

SET 6 - INTERIOR - PAIR

MEDICAL STORAGE