

**SECTION 101419
DIMENSIONAL LETTER SIGNAGE**

PART 1 GENERAL**1.01 SECTION INCLUDES**

- A. Dimensional letter signage.

1.02 SUBMITTALS

- A. See Section 013000 - Administrative Requirements for submittal procedures.
- B. Product Data: Manufacturer's product literature for each type of dimensional letter sign, indicating style, font, colors, locations, and overall dimensions of each sign.
- C. Shop Drawings:
 - 1. Include dimensions, locations, elevations, materials, text and graphic layout, and attachment details.
- D. Selection Samples: Where materials, colors, and finishes are not specified, submit two sets of selection charts or chips.
- E. Verification Samples: Submit samples showing colors and finishes specified.
- F. Manufacturer's qualification statement.

1.03 QUALITY ASSURANCE

- A. Manufacturer Qualifications: Company specializing in manufacturing the products specified in this section with minimum three years of documented experience.

1.04 DELIVERY, STORAGE, AND HANDLING

- A. Package dimensional letter signs as required to prevent damage before installation.
- B. Store under cover and elevated above grade.

PART 2 PRODUCTS**2.01 MANUFACTURERS**

- A. Dimensional Letter Signs:
 - 1. Awning and Sign Contractors: www.ascfabricators.com/#sle.
 - 2. CityScapes Inc; _____: www.cityscapesinc.com/#sle.
 - 3. FASTSIGNS International, Inc; _____: www.fastsigns.com/#sle.
 - 4. Inpro Corporation; _____: www.inprocorp.com/#sle.

2.02 DIMENSIONAL LETTERS

- A. Applications: Building identification.
 - 1. Use individual metal letters.
 - 2. Mounting Location: Exterior as indicated on drawings.
 - 3. Allow for total of 21 letters, 12 inches (300 mm) high. and 2 numbers, 48 inches 1200 mm high.
- B. Metal Letters:
 - 1. Material: Aluminum sheet, fabricated reverse channel.
 - 2. Thickness: Manufacturer's standard for letter size.
 - 3. Letter Height: 12 inches (150 mm).
 - 4. Number Height: 48 inches 1200 mm.
 - 5. Text and Typeface:
 - a. Character Font: Helvetica, Arial, or other sans serif font.
 - 6. Finish: Brushed, satin.
 - 7. Color: As selected.
 - 8. Mounting: Projected mount with collars.

2.03 ACCESSORIES

- A. Concealed Screws: Noncorroding metal; stainless steel, galvanized steel, chrome plated, or other.

PART 3 EXECUTION

3.01 EXAMINATION

- A. Verify that substrate surfaces are ready to receive work.
- B. Notify Architect if conditions are not suitable for installation of signs; do not proceed until conditions are satisfactory.

3.02 INSTALLATION

- A. Install in accordance with manufacturer's instructions.
- B. Install with horizontal edges level.

END OF SECTION