



1 DEMOLITION PLAN - FIRST FLOOR
1/8" = 1'-0"



GENERAL NOTES

1. DEMOLITION CONTRACTOR SHALL PROVIDE FIRE EXTINGUISHERS AT EVERY LEVEL AND AS THE FIRE SAFETY CODE REQUIRES AT ALL TIMES
2. CONTRACTOR IS RESPONSIBLE FOR ALL TEMPORARY SHORING DURING CONSTRUCTION AND PERMANENT SHORING
3. WALLS ARE DIMENSIONED FROM FACE OF FRAMING UNLESS OTHERWISE NOTED
4. CONTRACTOR SHALL SNAKE ALL EXISTING SITE DRAINS, PIPES, AND DOWNSPOUTS
5. NO KEYED LOCKS ARE PERMITTED ON EGRESS SIDE OF EXTERIOR EXIT DOORS.
6. THE CONTRACTOR SHALL PERMANENTLY IDENTIFY ALL FIRE RATED WALLS REQUIRED TO HAVE PROTECTED OPENINGS, CORRIDOR PARTITIONS, SMOKESTOP PARTITIONS, HORIZONTAL EXIT PARTITIONS AND EXIT ENCLOSURES EITHER BY INSTALLING SIGNS FOLLOWING: FIRE AND SMOKE BARRIER - PROTECT ALL OPENINGS TO ENSURE PROPER INSTALLATION OF RATED WALL ASSEMBLY AT REPAIRED AREAS.
7. CONTRACTOR SHALL PLAN & IMPLEMENT A PROPER FIRE SAFETY PROGRAM & TRAIN WORKERS FOR MEASURES IN THE CASE OF AN EMERGENCY. FIRE EXTINGUISHERS SHALL BE EASILY VISIBLE & ACCESSIBLE AT ALL AREAS OF WORK AT ALL TIMES.
8. INTENTIONALLY LEFT BLANK
9. INTENTIONALLY LEFT BLANK

DEMOLITION NOTES

- | | | |
|----------------------------|----------------------------|-----------------------------|
| 1 INTENTIONALLY LEFT BLANK | 5 INTENTIONALLY LEFT BLANK | 9 INTENTIONALLY LEFT BLANK |
| 2 INTENTIONALLY LEFT BLANK | 6 INTENTIONALLY LEFT BLANK | 10 INTENTIONALLY LEFT BLANK |
| 3 INTENTIONALLY LEFT BLANK | 7 INTENTIONALLY LEFT BLANK | 11 INTENTIONALLY LEFT BLANK |
| 4 INTENTIONALLY LEFT BLANK | 8 INTENTIONALLY LEFT BLANK | 12 INTENTIONALLY LEFT BLANK |

PARTITION LEGEND

- SEE SECTIONS FOR DETAILS
- 2-HOUR DEMISING FIRE BARRIER UL # U347
 - 1-HOUR FIRE BARRIER UL # U337
 - INTERIOR PARTITION