



ENTRY FOUNDATION PLAN
SCALE: 1/4" = 1'-0"

FOUNDATION PLAN NOTES:

1. TOP OF ALL FOOTINGS SHALL BE -1'-0" BELOW FINISHED FLOOR, U.N.O.
2. REFER TO ARCH'L DRAWINGS FOR LOCATION OF CURBS, EXTERIOR SLABS, DRAINAGE, RAMPS, STEPS, WALKS, ETC.
3. BUILDING SLAB IS NOT DESIGNED TO SUPPORT CRANE LOADS, CONCRETE MIXING TRUCKS, OR OTHER SPECIFIC CONSTRUCTION LOADINGS.
4. FOOTINGS/PIERS SHALL BE CENTERED ON THE CENTERLINE OF THE WALL AND/OR COLUMNS, U.N.O.
5. REFER TO ARCHITECTURAL PLANS FOR DIMENSIONS NOT SHOWN. COORDINATE SLAB ELEVATIONS AND SLOPES WITH ARCHITECTURAL PLANS.

PILE SCHEDULE			
MARK	RADIUS	HEIGHT	REINFORCEMENT
P20	1' - 8"	4' - 6"	(8) #5 VERTICAL, #3 CIRCULAR TIES @ 8" O.C.

FOOTING SCHEDULE				
MARK	LENGTH	WIDTH	THICKNESS	REINFORCEMENT
F4.5	4' - 6"	4' - 6"	1' - 0"	(5) #5 E.W.